
Reset | Download 3D Model



Code Number	CCM	* L 1 mm./inch.	* L 2 mm./inch.	* L 3max mm./inch.
151F0528	80	87.0[3.43]	109.0[4.29]	max. 131.3[5.17]
151F0529	100	90.4[3.56]	112.4[4.43]	max. 134.7[5.30]
151F0530	125	94.8[3.73]	116.8[4.60]	max. 139.1[5.48]
151F0531	160	100.8[3.97]	122.8[4.83]	max. 145.1[5.71]
151F0532	200	107.8[4.24]	129.8[5.11]	max. 152.1[5.99]
151F0533	250	116.5[4.59]	138.5[5.45]	max. 160.8[6.33]
151F0534	315	127.8[5.03]	149.8[5.90]	max. 172.1[6.78]
151F0609	400	141.4[5.57]	163.4[6.43]	max. 185.7[7.31]

C: Drain connection
G 1/4; 12[0.47] deep
D: M10; 13[0.51] deep
E: G 1/2; 16[0.63] deep

Tolerance for basic dimensions = ±1 mm (0.04 inch)

Altered	Reason	Date
-	-	-

Scale 1:1 | Projection | Date 2014.12.08 | Design MP | Approb.

OMSW
ø35 tapered

No. 8_151D0591

Confidential: Property of Danfoss (Nordborg) A/S, Denmark. Not to be handed over to, copied or used by third party. Two- or three dimensional reproduction of contents to be authorized by Danfoss (Nordborg) A/S. Danfoss (Nordborg) A/S can accept no responsibility for possible errors on drawings. Danfoss (Nordborg) A/S reserves the right to alter products already on order or provided that such alterations can be made without subsequential changes being necessary in specifications already agreed.