

Category	151B3127	Units
Type	OMV	
Motor size	500	
Geometric displacement	499,6 [30.49]	cm ³ [in]
Max speed cont	400	rpm
Max speed int	480	rpm
Max torque cont	1460 [12920]	Nm [lbf in]
Max torque int	1760 [15580]	Nm [lbf in]
Max output power cont	53,5 [71.7]	kW [hp]
Max output power int	64,0 [85.8]	kW [hp]
Max pressure drop cont	200 [2900]	bar [psi]
Max pressure drop int	240 [3480]	bar [psi]
Max pressure drop peak	280 [4060]	bar [psi]
Max oil flow cont	200 [52.8]	l/min [gpm]
Max oil flow int	240 [63.4]	l/min [gpm]
Max starting pressure with unloaded shaft	8 [115]	bar [psi]
Min starting torque at max press drop cont	1130 [10000]	Nm [lbf in]
Min starting torque at max press drop int	1360 [12040]	Nm [lbf in]
Max inlet pressure cont	210 [3050]	bar [psi]
Max inlet pressure int	250 [3630]	bar [psi]
Max inlet pressure peak	300 [4350]	bar [psi]
Max return pressure with drain line cont	140 [2030]	bar [psi]
Max return pressure with drain line int	175 [2540]	bar [psi]
Max return pressure with drain line peak	210 [3050]	bar [psi]
Holding torque		Nm [lbf in]
Min brake release pressure		bar [psi]
Max pressure in brake line		bar [psi]
Max pressure in drain line		bar [psi]